



The metal spacer ring enclosed (HILFR15) **IS REQUIRED** for use with **ALL Toyota Hilux and Fortuner** to maintain standard spring seat height.

The spacer ring is **NOT** required for **Toyota Prado**, but may be used to achieve extra ride height from normal increase. Consider that an Ironman coil spring will already provide extra lift from standard and the spacer will add more.

TIP: Due to the ratio effect of independent suspension, effective lift is double the spacer thickness.

FIT SPACER RING BEFORE INSTALLING COIL SPRING SEAT

Align cutout in spring seat toward front of vehicle, this will provide sufficient clearance for the anti-roll bar.

Unnecessary fitment of spacer rings may lift vehicle too high. Independent suspension must have at least 60mm downward travel remaining after the suspension lift.



The metal spacer ring enclosed (HILFR15F) **IS REQUIRED** for use with **ALL Toyota Hilux and Fortuner** to maintain standard spring seat height.

The spacer ring is **NOT** required for **Toyota Prado**, but may be used to achieve extra ride height from normal increase. Consider that an Ironman coil spring will already provide extra lift from standard and the spacer will add more.

TIP: Due to the ratio effect of independent suspension, effective lift is double the spacer thickness.

FIT SPACER RING BEFORE INSTALLING COIL SPRING SEAT

Align cutout in spring seat toward front of vehicle, this will provide sufficient clearance for the anti-roll bar.

Unnecessary fitment of spacer rings may lift vehicle too high. Independent suspension must have at least 60mm downward travel remaining after the suspension lift.